

### AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application. Where claims have been amended, deletions are indicated by ~~[[double brackets]]~~ or ~~strikethrough~~, and additions are indicated by underlining:

#### In the claims

1. (Currently Amended): A delivery catheter for a gastric reduction system, the delivery catheter comprising:

an elongate torqueable and flexible tube having a back end and a front end;

a needle translatably disposed within the tube, with the needle having a penetrating tip; ~~[[and]]~~

at least one anchor translatably disposed within the needle, and moveable out of the penetrating tip of the needle; and

a coil on a front end of a shaft that is translatably disposed within a lumen in said tube, said coil being extendible out of the front end of the tube.

2. (Previously presented): The delivery catheter of claim 1, wherein the tube is formed of a braided wire.

3. (Previously presented): The delivery catheter of claim 1, wherein the tube contains a plurality of slots disposed substantially perpendicular to a longitudinal axis of the tube.

4. (Previously presented): The delivery catheter of claim 3, wherein the slots are formed in a sinusoidal pattern.

5. (Previously presented): The delivery catheter of claim 3, wherein the slot density is increased near a distal end of the tube.

6. (Cancelled).

7. (Cancelled).

8. (Currently Amended): The delivery catheter of claim [[7]] 1, wherein the coil includes a sharpened distal tip to facilitate tissue penetration.

9. (Currently Amended): The delivery catheter of claim [[7]] 1, wherein the coil comprises a plurality of coils that form a central opening for the passage of the needle.

10. (Currently Amended): The delivery catheter of claim [[7]] 1, wherein the coil and needle are substantially coaxial.

11. (Cancelled).

12. (Original) The delivery catheter of claim 1, further comprising a push rod translatablely disposed within the needle and adapted to push the anchor out of a distal end of the needle.

13-45. (Cancelled).

46. (Currently Amended): A catheter comprising:  
a flexible tube having a front end and a back end;  
a needle within the tube and having a tip extendible out of the front end of the tube;  
at least one anchor positioned within the flexible tube and moveable out of the flexible tube during a surgical procedure; [[and]]  
a suture connected to one or more of the anchors, and with the suture extending within the tube towards the back end of the tube; and  
a coil on a front end of a shaft that is translatablely disposed within a lumen in said tube, said coil being extendible out of the front end of the tube.

47. (Previously presented): The catheter of claim 46 wherein the tube is torqueable and is formed of braided wire.

48. (Previously presented): The catheter of claim 46 wherein the tube contains a plurality of slots extending substantially perpendicular to a longitudinal axis of the tube, to increase the flexibility of the tube.

49. (Currently Amended): The catheter of claim ~~[[45]]~~ 46, wherein said coil has ~~further comprising a coil at the front end of the flexible tube, with the coil having a sharp tip.~~

50. (Previously presented): The catheter of claim 49 with the needle having a penetrating tip adjacent to the front end of the flexible tube.

51. (Previously presented): The catheter of claim 49 with the needle positioned to extend out of the front end of the flexible tube and through the coil.

52. (Previously presented): The catheter of claim 46 further comprising a push rod longitudinally moveable within the needle for pushing one or more anchors out of the tip of the needle.

53. (Previously presented): The catheter of claim 46 with the needle having a non-coring tip.

54. (Previously presented): The catheter of claim 46 with the tube having a coating of fluorine resins.

55. (Currently Amended): A catheter comprising:  
a flexible and torqueable tube having a front end and a back end;  
a needle within the tube and having a piercing tip extendible out of the front end of the tube;

one or more anchors stored within the tube and moveable out of the tube for placement during a surgical procedure; [[and]]  
a suture connected to the anchor and leading out towards the back end of the tube;  
and  
a coil on a front end of a shaft that is translatably disposed within a lumen in said tube, said coil being extendible out of the front end of the tube.

56. (Previously presented): The catheter of claim 55 wherein the tube having through slots to increase the flexibility of the tube.

57. (Cancelled).

58. (Previously presented): The catheter of claim 55 further comprising a push rod longitudinally moveable within the needle for pushing an anchor out of the tip of the needle.

59. (Currently Amended): A catheter comprising:  
a flexible and torqueable tube having a front end and a back end;  
a handle attached adjacent to the back end of the tube;  
a hollow needle within the tube and having a piercing tip extendible out of the front end of the tube;  
one or more anchors within the needle, with the anchor moveable out of the piercing tip of the needle;  
an anchor ejector within the needle;  
a suture connected to the anchor and leading out towards the handle;  
a needle control on the handle linked to the needle, for moving the needle within the tube; [[and]]  
an anchor ejector control on the handle linked to the anchor ejector; and  
a coil on a front end of a shaft that is translatably disposed within a lumen in said tube, said coil being extendible out of the front end of the tube.

60. (Currently Amended): A catheter comprising:  
a flexible tube having a front end and a back end;  
a needle within the tube and having a tip extendible out of the front end of the tube;  
at least one anchor positioned within the needle and moveable out of the needle tip  
during a surgical procedure; [[and]]  
a suture connected to one or more of the anchors, and with the suture extending  
within the tube towards the back end of the tube; and  
a coil on a front end of a shaft that is translatably disposed within a lumen in said  
tube, said coil being extendible out of the front end of the tube.